$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 1 of 6 SDS-045

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.1

SDS Revision Date: 2/8/2016

.1	Product Name:	OPI MICROBOND UV LIGHT CLEANER	
1.2	Chemical Name:		
		Alcohol Solution	
1.3	Synonyms:	NA	
1.4	Trade Names:	MBM52, MBM56, MBM58	
1.5	Product Use:	Professional Or Sundry Use Only	
1.6	Distributor's Name:	OPI Products, Inc.	
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA	
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)	•
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776	

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.

Classification: Flam. Liq. 2; Eye irrit. 2A; STOT SE 3

<u>Hazard Statements</u> (H): H225 – Highly flammable liquid and vapor. H319 – Causes serious eye irritation. H336 – May cause drowsiness or dizziness.

Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 - In case of fire, CO₂, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

				EXPOSURE L				SURE LI	LIMITS IN AIR (mg/m³)				
					AC	GIH		NOHSC			OSHA		
					ppm		ppm			ppm			ļ
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	60-100	400	500	400	500	NF	400	500	2000	400 TWA
ISOPROPTE ALCOHOL	Flammable Liq	uids 2; Skin Irritat	ion 3; Eye Irritati	ion 2A; Spe	ecific Ta	arget O	rgan To	xicity -	Single	Exposu	ıre 3; H	225, H3	316, H319
DARELIM/EDACDANCE	NA	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
PARFUM/FRAGRANCE													
CL CAZAO (A CID VIOLET DA)	6408-63-5	NA	229-062-9	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 61710 (ACID VIOLET 34)													
CI 18055 (ACID VIOLET 7)	4321-69-1	QJ6000000	224-352-1	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Eyes:	If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove all contaminated clothing, including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
		Inhalation:	Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

 $0.9 \cdot 1$

SAFETY DATA SHEET

Page 2 of 6 SDS-045

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 4. FIRST AID MEASURES - cont'd Effects of Exposure: 4.2 If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or Eyes: transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions Skin: (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue may occur. 4.3 Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 44 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 The material may accentuate any pre-existing dermatitis condition. Methylparaben contained in very small amounts in this product, may be a mild allergen to some sensitive individuals. 46 Target Organs: Eyes, Skin, Respiratory System. Pre-existing dermatitis, other skin conditions, and disorders of the 47 Medical Conditions **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 **PHYSICAL HAZARDS** 0 PROTECTIVE EQUIPMENT В EYES SKIN 5. FIREFIGHTING MEASURES 5 1 Fire & Explosion Hazards: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. Extinguishing Methods: 5.2 CO₂, Halon (if permitted), Dry Chemical, Foam, as authorized. 5.3 Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3(Y)E Hazard Identification Number: 33 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Spills Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 72 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

$O \cdot P \cdot I$

Reproductive Toxicity:

SAFETY DATA SHEET

Page 3 of 6 SDS-045

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits ACGIH NOHSC OSHA OTHER ppm (mg/m³) FS FS. FS. TLV STEL PEL STEL CHEMICAL NAME(S) TWA STEL PEAK IDLH 2000 400 TWA ISOPROPYL ALCOHOL 400 500 400 500 NF 400 500 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Controls: Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.4 Eve Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. Body Protection: 8.6 However, no special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Violet liquid Medicinal alcoholic odor Odor Threshold: 9.3 NA 9.4 NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 181 °F Range: 9.7 Flashpoint 12 °C (53 °F) 9.8 Upper/Lower Flammability 2.0 - 12.7 9.9 Vapor Pressure: NA 9.10 Vapor Density NA 9.11 Relative Density: NA 9.12 Solubility: Soluble Partition Coefficient (log Pow): 9.13 NA Autoignition Temperature: 852 °F 9.14 9.15 Decomposition Temperature: NA 9.16 Viscosity: < 500 cPs 9.17 Other Information: Evaporation Rate < 1.0 (n-BuAc = 1.0) 10. STABILITY & REACTIVITY 10.1 Stability Relatively stable under ambient conditions when stored properly. 10.2 Hazardous Decomposition If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic Products: gases (e.g., oxides of carbon & nitrogen). 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame. 10.5 Incompatible Substances: Strong oxidizers, peroxides or strong acids. 11. TOXICOLOGICAL INFORMATION Inhalation: YES Absorption: YES Routes of Entry: 11.1 Inaestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity See Section 4.5 11.5 Suspected Carcinogen: This product contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as a Group 3 carcinogen by the IARC. 11.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans.

This product is not reported to cause reproductive effects in humans.

 $O \cdot P \cdot I$

SAFETY DATA SHEET

Page 4 of 6 **SDS-045**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 11. TOXICOLOGICAL INFORMATION - cont'd Irritancy of Product: See Section 4.3 11.7 11.8 Biological Exposure Indices: 11 9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: 12.1 The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated halflife in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. Effects on Plants & Animals: 12.2 There are no specific data available for this product. Effects on Aquatic Life: 12.3 There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste disposal must be in accordance with appropriate Federal, state, and local regulations. Waste Disposal: 13.1 U.S. EPA Waste Number: D001 (characteristic - ignitable) 13.2 Special Considerations 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1 | 49 CFR (GND): | I IN12140 ISODRODANIO UN1219, ISOPROPANOL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D - until 01/01/2021 14.2 IATA (AIR): ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1219, ISOPROPANOL, 3, II (IP VOL ≤ 1.0 L) 14.3 IMDG (OCN): UN1219, ISOPROPANOL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1219, ISOPROPANOL, 3, II, LTD QTY (IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) ADR/RID (EU): 14.5 UN1219, ISOPROPANOL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) SCT (MEXICO): 14.6 UN1219, ISOPROPANOL, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1219, ISOPROPANOL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains Isopropyl Alcohol, a substance subject to SARA Title III, Section 313 reporting requirements. Requirements SARA Threshold Planning 15 2 There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory 15 4 **CERCLA Reportable Quantity** NA 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable, Other Toxic Effects). 15.7 State Regulatory Information: Isopropanol is listed on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Isopropanol: Flammable, Irritant (F, Xi). Risk Phrases (R) 11-36-66-67 Highly flammable. Irritating to eyes. Vapors may cause drowsiness and dizziness. Safety Phrases (S) 2-9-16-26 Keep out of reach of children. Keep container in well-ventilated place. Keep away from sources of ignition. In case of contact with skin, wash immediately with plenty of water.

 $0.9 \cdot 1$

SAFETY DATA SHEET

Page 5 of 6 SDS-045

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 16. OTHER INFORMATION DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES 16 1 Other Information: EYE IRRITATION. Keep away from heat/sparks/open flame/hot surfaces - No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. Avoid eye contact. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN. Terms & Definitions: See last page of this Safety Data Sheet. 16.2 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: **OPI Products, Inc.** 13034 Saticoy Street).P.I No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 **SDS-045**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/8/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienists			
TLV Threshold Limit Value			
OSHA U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit			
IDLH Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has		
stopped receives manual chest compressions and breathing to circulate b			
	and provide oxygen to the body.		

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1 Slight Hazard			
2 Moderate Hazard			
3	Severe Hazard		
4	Extreme Hazard		



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Ε			
F		THE THE	













Synthetic Apron



Full Face Respirator

Dust & Vapor Half-Mask Respirator

Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND Not Determined	
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:						
Autoignition Minimum temperature required to initiate combustion in air with no Temperature source of ignition							
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume explode or ignite in the presence of an ignition source							
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ох	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	J.S. Department of Transportation					
TC	Fransport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(@	(®		(R)
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

13		M	*		\$	×	×
С	E	F	Ν	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\diamondsuit		(
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment