$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 1 of 6 SDS-061

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.1

SDS Revision Date: 2/8/2016

	1. PRODUCT & COMPANY IDENTIFICATION						
1.1	Product Name:	OPI NAIL ADHESIVE					
1.2	Chemical Name:	Cyanoacrylate Mixture					
1.3	Synonyms:	NA NA					
1.4	Trade Names:	NA 940, NA 941, NA947, NA 948					
1.5	Product Use:	Professional or Sundry Use Only					
1.6	Distributor's Name:	OPI Products, Inc.					
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA					
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)					
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776					

2. HAZARDS IDENTIFICATION

.1 Hazard Identification: This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).

WARNING! CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION.

Classification: Skin Irrit. 2; Skin Sens. 1A; Eye Irrit. 2A; STOT SE 3

to a licensed treatment, storage or disposal facility (TSDF).

Hazard Statements (H): H315 – Causes skin irritation. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H335 – May cause respiratory irritation. Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P261 – Avoid breathing fume/ mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO₂, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					AC	GIH		NOHSC			OSHA		
					pp	om		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHYL-2 CYANOACRYLATE	7085-85-0	UD3330050	230-391-5	60-100	(0.2)	NA	NF	NF	NF	NA	NA	NA	
ETITIE-2 CTANOACKTEATE	Skin Irrit.2; Eye	Skin Irrit.2; Eye Irrit. 2; STOT SE 3; H315, H319, H335											
POLY (METHYLMETHACRYLATE)	9011-14-7	TR0400000	201-297-1	7.0-13	100	NA	NF	NF	NF	100	NA	NA	MMA
Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; H315, H319, H335													
ISOPROPYL CYANOACRYLATE	10586-17-1	NA	NA	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISSURGE TE STANDAGKTEATE													
CALCIUM PANTOTHENATE	137-08-6	RU4375000	205-278-9	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	

4. FIRST AID MEASURES

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	This product bonds skin immediately. Do not pull. Peel slowly using acetone, (use lukewarm water only for product removal, if skin bonding has occurred near the eyes). If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. May bond skin to clothing and may release heat, causing burns. Cool burned area immediately with cold water. If clothing adheres to skin, do not pull; peel slowly under lukewarm water. Consult a physician for treatment of burns.
		Eyes:	Contact a physician immediately. Do not try to open the eye. Flush with cool water for at least 15 minutes opening and closing eyelids to ensure thorough irrigation. If irritation persists, contact a physician.
		Inhalation:	Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.
	•		

$0.9 \cdot 1$

SAFETY DATA SHEET

Page 2 of 6 SDS-061

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 4. FIRST AID MEASURES - cont'd If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system 42 Effects of Exposure: Ingestion: Vapor of this product may be mildly to moderately irritation to the eyes. Symptoms of overexposure may Eyes: include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged or repeated skin contact. Skin: May bond skin to clothing and release heat, causing burns. Inhalation: Inhalation of vapors is unlikely under normal conditions of use. Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Symptoms of skin overexposure in some sensitive individuals may include redness, itching, and irritation of affected 4.3 Symptoms of Overexposure areas. Overexposure of vapor in eyes may cause redness, itching and watering. 4.4 Acute Health Effects: Mild to moderate irritation to skin near affected areas. Vapor of this product may be mildly to moderately irritating to the eyes and mucous membranes. Symptoms of overexposure may include redness, itching, irritation and watering. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. None known. 4.5 Chronic Health Effects: Target Organs: Eyes, Skin, Respiratory System. 4.6 Pre-existing dermatitis, other skin conditions, and disorders of the 47 Medical Conditions HEALTH 2 Aggravated by Exposure: target organs (eyes, skin, and respiratory) **FLAMMABILITY** 1 2 **PHYSICAL HAZARDS** PROTECTIVE EQUIPMENT В SKIN **EYES** 5. FIREFIGHTING MEASURES Rapid polymerization may occur at very high temperatures. 5.1 Fire & Explosion Hazards: Extinguishing Methods: Water, CO₂, Halon (if permitted), Dry Chemical 5.2 When involved in a fire, this product will ignite readily and decompose to produce oxides of carbon 5.3 Firefighting Procedures: and nitrogen and hydrogen cyanide. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective 6.1 Spills For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Avoid prolonged or repeated skin contact. Avoid breathing vapors of this product. Use eye protection when using this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap & water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10, Stability and Reactivity). Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may 7.3 Special Precautions: contain residual amounts of this product; therefore, empty containers should be handled with care.

$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 3 of 6 SDS-061

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits **ACGIH** NOHSC OTHER ppm (mg/m³) FS FS. FS. CHEMICAL NAME(S)
ETHYL-2 CYANOACRYLATE STEL STEL TLV TWA STEL PEAK PEL IDLH (0.2)NA NF NF NF NA NA NΑ POLY 100 NA NF NF NF 100 NA NA (METHYLMETHACRYLATE) 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Controls: Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Safety glasses with side shields should be used with this product. This product is irritating to the 8.4 Eye Protection: eves. 8.5 Hand Protection: WARNING! THIS PRODUCT WILL BOND SKIN INSTANTLY. Therefore, the use of latex or rubber gloves is recommended. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. WARNING! THIS PRODUCT WILL BOND SKIN INSTANTLY. Therefore, the use of an apron is 8.6 Body Protection: recommended. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES Clear to slightly yellow liquid. Thixotropic gel. 9.1 Appearance: 9.2 Odor: Sharp, irritating acrylic odor 9.3 Odor Threshold: NA 9.4 NA Melting Point/Freezing Point: NA 9.5 Initial Boiling Point/Boiling 9.6 > 300 °F (> 149 °C) Range: 9.7 Flashpoint > 93 °C (> 200 °F) TCC 9.8 Upper/Lower Flammability NA Limits 9.9 Vapor Pressure: < 0.2 mm Hg > 3 @ 20 °C (68 °F) (Air = 1) Vapor Density Relative Density: 9.11 NA 9.12 Solubility Insoluble in water 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA 9.15 Decomposition Temperature: NA Viscosity: 9.16 Low viscosity. 9.17 Other Information: Polymerizes in water. 10. STABILITY & REACTIVITY Stable under ambient conditions when stored properly (See Section 7, Storage and Handling). Stability: 10.1 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases and hydrogen cyanide (e.g., CO, CO2, HCN). 10.3 Hazardous Polymerization: May occur, if exposed to extremely high temperatures or exposed to moisture. Exposure to or contact with extreme temperatures, strong light sources or incompatible materials 10.4 Conditions to Avoid: Incompatible Substances: This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or 10.5 muriatic acids), or strong bases (e.g., lye, potassium hydroxide). 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry Inhalation: YES Absorption: YES Ingestion: YES This product has NOT been tested on animals to obtain toxicological data. There are toxicology data for the 11.2 Toxicity Data: components of this product, which are found in the scientific literature. This data has not been presented in this document. 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: See Section 4.5 11.4 This product contains Poly(Methylmethacrylate), which is not carcinogenic to humans but is listed as a Group 3 11.5 Suspected Carcinogen: carcinogen by IARC. 11.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.

 $\mathbf{J} \cdot \mathbf{P} \cdot \mathbf{I}$

SAFETY DATA SHEET

Page 4 of 6

SDS-061 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 11. TOXICOLOGICAL INFORMATION - cont'd Irritancy of Product: See Section 4.3 11.7 Biological Exposure Indices: 11.8 NF 11.9 Physician Recommendations: Treat Symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. 12.2 Effects on Plants & Animals: There are no specific data available for this product. There are no specific data available for this product; however, very large releases of this product may be harmful or fatal 123 Effects on Aquatic Life: to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with federal, state, and local regulations. 13.2 Special Considerations 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): NOT REGULATED UN3334, AVIATION REGULATED LIQUID, N.O.S. (ethyl cyanoacrylate), 9 (IP VOL ≤ 0.5 L) 14.2 IATA (AIR): IMDG (OCN): 14.3 NOT REGULATED 14.4 TDGR (Canadian GND): **NOT REGULATED** 14.5 ADR/RID (EU): **NOT REGULATED** 14 6 SCT (MEXICO): NOT REGULATED 14.7 ADGR (AUS): **NOT REGULATED** This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirements 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: The components of this product are listed on the TSCA Inventory. 15.3 TSCA Inventory Status: 15.4 CERCLA Reportable Quantity NA 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics) 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. 15.7 State Regulatory Information: Ethyl cyanoacrylate is found on the following state criteria list: New Jersey Right-to-Know List (NJ). Poly(methylmethacrylate) is found on the following state criteria list: NJ and Pennsylvania Right-to-Know List (PA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC. 15.8 Other Requirements: Ethyl Cyanoacrylate: Irritant (Xi). Risk Phrases (R): 36/37/38-43 - Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. Safety Phrases (S): 2-24/25-26-46 Keep

away from children. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice

Poly(methylmethacrylate): Harmful (Xn). Risk Phrases (R): 20/22 Harmful by inhalation and if swallowed. Safety Phrases (S): 22-24/25-36 Do not breathe dust. Avoid contact with skin and

immediately and show this MSDS or container label.

eyes. Wear suitable protective clothing.

 $O \cdot P \cdot I$

SAFETY DATA SHEET

Page 5 of 6 SDS-061

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.1 SDS Revision Date: 2/8/2016 16. OTHER INFORMATION WARNING! CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE 16 1 Other Information: IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. Do not store near eye drops. Eye irritant. If eye contact occurs, flush immediately with water and seek medical attention. BONDS SKIN INSTANTLY. If skin bonds, do not pull - peel apart gently using acetone. Avoid contact with fabrics as heat may occur. Keep container tightly closed. P261 -Avoid breathing fume/ mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other 16.3 Disclaimer: government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. OPI Products, Inc. 16.4 Prepared for: 13034 Saticoy Street).P.I No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

SAFETY DATA SHEET

Page 6 of 6 **SDS-061**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/8/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
TLV Threshold Limit Value				
OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit				
IDLH Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

FLAMMABILITY PHYSICAL HAZARDS PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
E			
F			







Splash Goggles





D



Synthetic Apron

Protective Clothing & Full Suit



Full Face Respirator

Dust & Vapor Half-Mask Respirator

Full Face Respirator



OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature Minimum temperature required to initiate combustion in air with no source of ignition						
LEL Lower Explosive Limit - lowest percent of vapor in air, by vol explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ох	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	TSCA U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(4)	(3)	\odot	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		M	*		\$	×	×
С	Е	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment