$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 1 of 6 **SDS-077**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.2

SDS Revision Date: 2/8/2016

1.1	Product Name:	POLISH REMOVER	
1.2	Chemical Name:	Acetone Solution	
1.3	Synonyms:	NA NA	
1.4	Trade Names:	AL 401, AL 403, AL 404, AL 406, AL 407, AL 409	
1.5	Product Use:	Cosmetic Use Only	
1.6	Distributor's Name:	OPI Products, Inc.	
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA	
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN XXXXX)	
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776	

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a hazardous substance but not as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION.

Classification: Flam. Liq. 2; Skin Sens. 1A

<u>Hazard Statements</u> (H): H225 – Highly flammable liquid and vapor. H317 – May cause an allergic skin reaction.

Precautionary Statements (P): P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P261 – Avoid breathing fumes/mists/vapours/spray. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P281 – Use personal protective equipment as required. P302+P352 – IF ON SKIN: Wash with soap and water. P308+P313 - IF exposed or concerned: Get medical advice/attention. P333+P313 – If skin irritation or a rash occurs: Get medical advice/attention. P321 – Specific treatment (See Section 4.1 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P405 – Store locked up. P501 – Dispose of contents/container to licensed waste management facility (See Section 13.1 of this Safety Data Sheet).



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m ³)								
				ACGIH		NOHSC		OSHA					
	CAS No. R			%	ppm		ppm		ppm]		
CHEMICAL NAME(S)		RTECS No.	EINECS No.		TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
ACETONE	67-64-1	AL3150000	200-662-2	60-100	1800	NA	1185	2375	NF	2400	NA	2500	
ACETONE	Flam. Liq. 2; E	ye Irrit. 2; STOT	SE 3, H225, H3	19, H336									
AOLIA (MATER)	7732-18-5	ZC0110000	231-191-2	15-40	NA	NA	NF	NF	NF	NA	NA	NA	
AQUA (WATER)													
ALOE BARBADENSIS LEAF	85507-69-3	NA	287-390-8	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
EXTRACT				•		•	•	•	•	•	•	•	
EDACDANICE (DADELINA)	NA	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
FRAGRANCE (PARFUM)													
ETHYLHEXYL	5466-77-3	UD3392732	226-775-7	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
METHOXYCINNAMATE			•										•
ARAVI CININIARANI	122-40-7	GD6850000	204-541-5	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
AMYL CINNAMAL	Acute Tox. Or	al 5; Skin Sens.	1; Aquatic Acute	2; Aquatic	Chronic	2; H30	3, H317	7, H411					
LIEVO (OININIAMA)	101-86-0	GD6560000	202-983-3	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	ALLERGEN
HEXYL CINNAMAL	Skin Sens. 1E	; Aquatic Chronic	c 2; H317, H411	•		•	•	•	•	•	•	•	
01.045=0.400=511.5)	4403-90-1	DB5044000	224-546-6	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 61570 (GREEN 5)			,			ı	1	1			1		•
	8003-22-3	GE5925000	232-318-2	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 47000 (YELLOW 1)		12222000	1-0- 0.02		,	,	1	1	1				

Page 2 of 6 SAFETY DATA SHEET **SDS-077** Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.2 SDS Revision Date: 2/8/2016 4. FIRST AID MEASURES First Aid: Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water Eyes: for at least 15 minutes. If irritation occurs, contact a physician. Skin: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. Inhalation: 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression. The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or Eyes: transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions Skin: (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue 4.3 Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 4.4 Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 4.5 Chronic Health Effects: The material may accentuate any pre-existing dermatitis condition. 4.6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 PHYSICAL HAZARDS 0 В PROTECTIVE EQUIPMENT **EYES** SKIN 5. FIREFIGHTING MEASURES 5.1 Fire & Explosion Hazards: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. 5.2 Extinguishing Methods: CO₂, Halon (if permitted), Dry Chemical, Foam HazChem Code: 3YE Hazard Identification Number: 33 5.3 Firefighting Procedures: First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. **ACCIDENTAL RELEASE MEASURES** 6.1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). For small spills (e.g., < 1 gallon (3.79 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., ≥ 1 gallon (3.79 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing

promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal

sewers and open bodies of water.

$\mathbf{J} \cdot \mathbf{P} \cdot \mathbf{I}$

10.3

10.4

10.5

Hazardous Polymerization:

Incompatible Substances:

Conditions to Avoid:

Page 3 of 6

SAFETY DATA SHEET **SDS-077** Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 72 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). 7.3 Special Precautions Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION ACGIH NOHSC OTHER 8.1 Exposure Limits: ppm (mg/m³) FS-FS-FS-CHEMICAL NAME(S) TI V STFI TWA <u>STÉ</u>L PEAK PFI STEL IDLH **ACETONE** 1800 NA 1185 2375 NF 2400 NA 2500 **ETHYLHEXYL** NA NA NF NF NF NA NA NA **ALLERGEN METHOXYCINNAMATE** AMYL CINNAMAL NA NA NF NF NF NA NA NA ALLERGEN HEXYL CINNAMAL NA NA NF NF NF NA NA NA ALLERGEN 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure Controls: that an eyewash station, sink or washbasin is available in case of exposure to eyes Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia. Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Hand Protection: 8.5 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the EU member states. Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Green, translucent liquid 9.2 fragrant, mint-like odor 9.3 Odor Threshold: ND 9.4 NA 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling 56.1 °C (133 °F) Range: 9.7 Flashpoint: - 14 °C (6.8 °F) 9.8 Upper/Lower Flammability LEL: 2.5 %; UEL: 12.8 Limits: 9.9 Vapor Pressure: NA Vapor Density: NA 9.11 Relative Density: 0.78 - 0.869.12 Solubility Soluble in water 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA Decomposition Temperature: 9.15 NA 9 16 Viscosity < 500 cPs 9.17 Other Information: Evaporation Rate: < 1.0 (n-BuAc = 1.0) 10. STABILITY & REACTIVITY 10.1 Stability: Stable under ambient conditions when stored properly (See Section 7, Storage and Handling). 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂).

May occur, if exposed to extremely high temperatures.

Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.

muriatic acids), or strong bases (e.g., lye, potassium hydroxide) and potassium t-butoxide.

This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or

$0.9 \cdot 1$

SAFETY DATA SHEET

Page 4 of 6 **SDS-077**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 3.2 SDS Revision Date: 2/8/2016 11. TOXICOLOGICAL INFORMATION Inhalation: YES Routes of Entry Ingestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. This data has not been presented in this document. 11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 Suspected Carcinogen: 11.5 This product contains Toluene and Isopropyl Alcohol, which are not carcinogenic to humans, but are listed as Group 3 carcinogens by IARC. 11.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3 11.8 Biological Exposure Indices: NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: 12.1 There are no specific data available for this product Effects on Plants & Animals: 12.2 There are no specific data available for this product. Effects on Aquatic Life: 12.3 There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION 49 CFR (GND): 14.1 UN1090, ACETONE, 3, II (IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) - until 12/31/2020 IATA (AIR): 14.2 \bigcirc or \bigcirc \bigcirc UN1090, ACETONE, 3, II, LTD QTY (IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) IMDG (OCN): 14.3 UN1090, ACETONE, 3, II, LTD QTY (IP VOL ≤ 1.0 L) TDGR (Canadian GND): 14.4 UN1090, ACETONE, 3, II, LTD QTY (IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L) ADR/RID (EU): UN1090, ACETONE, 3, II, LTD QTY (IP VOL ≤ 1.0 L) SCT (MEXICO): 14.6 UN1090, ACETONE, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1090, ACETONE, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 15. REGULATORY INFORMATION 15.1 SARA Reporting This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. Requirement 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory or are otherwise exempt. 15.4 CERCLA Reportable Quantity Acetone: 2,270 kg (5,000 lbs) 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2, D2B (Flammable Liquid, Other Toxic Effects)

$O \cdot P \cdot I$

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

http://www.shipmate.com

SAFETY DATA SHEET

SDS Revision: 3.2

Page 5 of 6 **SDS-077**

SDS Revision Date: 2/8/2016

15. REGULATORY INFORMATION – cont'd 15.7 Acetone is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air State Regulatory Information: Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), and Wisconsin Hazardous Substances List (WI). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 15.8 Other Requirements: The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC. Acetone: Highly Flammable (F+). Risk Phrases (R): 11-36-66-67 - Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapors may cause drowsiness and dizziness. Safety Phrases (S): 9-16-23-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Take precautionary measures against static discharges. HazChem Code: 2[Y]E. Poisons Schedule Number: S5 16. OTHER INFORMATION Other Information: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces - No Smoking. Keep container tightly closed. Avoid breathing fumes/mists/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. IF ON SKIN: Wash with soap and water. IF exposed or concerned: Get medical advice/attention. If skin irritation or a rash occurs: Get medical advice/attention. Specific treatment (See Section 4.1 of this Safety Data Sheet). Wash contaminated clothing before reuse. Store locked up. Use only as directed. Avoid eye contact. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions See last page of this Safety Data Sheet. 16.3 Disclaimer This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: OPI Products, Inc. 13034 Saticoy Street).P.I No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

SAFETY DATA SHEET

Page 6 of 6 **SDS-077**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 3.2

SDS Revision Date: 2/8/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

EXPOSURE LIMITS IN AIR:						
ACGIH American Conference on Governmental Industrial Hygienists						
TLV Threshold Limit Value						
OSHA U.S. Occupational Safety and Health Administration						
PEL	Permissible Exposure Limit					

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

IDLH Immediately Dangerous to Life and Health

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


CAS No. Chemical Abstract Service Number

0	Minimal Hazard			
1	1 Slight Hazard			
2 Moderate Hazard				
3 Severe Hazard				
4	Extreme Hazard			



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D			
Е			
F			





Splash Goggles





Dust & Vapor Half-

Mask Respirator

Synthetic Apron



Protective Clothing & Full Suit

Face Shield &

Protective Evewear

Dust Respirator

Full Face Respirator

ซืเ Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

NA	Not Available		
NR	No Results		
NE	Not Established		
ND Not Determined			
ML	Maximum Limit		
SCBA	Self-Contained Breathing Apparatus		

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard
U	IVIII III II
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(A)	@	\odot	®		Ř
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		M	*		®	X	X
С	Е	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\diamondsuit		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment