$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 1 of 7 SDS-250

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

		1. PRODUCT & COMPANY IDENTIFICATION	
1.1	Product Name:	GELCOLOR BY OPI – BASE GEL	
В	Chemical Name:	Solvent Mixture	
NA	Synonyms:	GC010	
1.4	Trade Names:	Gel Color by OPI – Base Gel	
1.5	Product Use:	Professional or Sundry Use Only	
1.6	Distributor's Name:	OPI Products, Inc.	
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA	
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)	
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776	

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

WARNING! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION.

Classification: Flam. Liq. 2; Skin Sens. 1A; Eye Irrit. 2A

<u>Hazard Statements</u> (H): H225 – Highly flammable liquid and vapor. H317 – May cause an allergic skin reaction. H320 – Causes eye irritation.

Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing dust/fume/gas/mist/vapours/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs - Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 - In case of fire, use CO₂, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE L	IMITS IN	AIR (m	g/m³)	
					AC	GIH		NOHSC	;		OSHA		
					pp	m		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	10-30	400	400	200	400	NF	NA	NA	2000	400 TWA
INTLACETATE	Flam. Liq. 2; E	Eye Irrit. 2; STOT	SE 3; H225, H3	19, H336									
SD ALCOHOL 40-B	64-17-5	KQ6300000	200-578-6	10-30	1000	1900	1880	NF	NF	1000	1900	3300	
D ALCOHOL 40-B	Flam. Liq. 2; I	1225											
DI-HEMA TRIMETHYLHEXYL DICARBAMATE	72869-86-4	NA	276-957-5	10-30	NA	NA	NF	NF	NF	NA	NA	NA	
	123-86-4	AF7350000	204-658-1	10-30	150	200	150	200	NF	200	200	1700	150 TWA
BUTYL ACETATE	Flam. Lig. 3: S	STOT SE 3; H226											
IEDTANIE	142-82-5	MI7700000	205-563-8	7.0-13	400	500	400	1640	NF	500	NA	750	
HEPTANE	Flam. Lig. 2: S	Skin Irrit. 2; STOT											
	9004-70-0	QW0970000	INA	≤ 5.0	(10)	NE	NF	NF	NF.	(10)	NE	NE	
IITROCELLULOSE	Flam. Lig. 2; I			1	()					()			
	25035-71-6	QW0970000	NA	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
OSYLAMIDE/EPOXY RESIN		•		•							1		•
IENAA	868-77-9	OZ4725000	212-782-2	≤ 3.0	NA	NA	NF	NF	NF	NA	NA	NA	
HEMA	Eye Irrit. 2; Sk	in Irrit. 2; Skin Se	ens. 1; H319, H3	15, H317			•			•			
HYDROXYPROPYL	27813-02-1	UD3422500	248-666-3	≤ 3.0	NA	NA	NF	NF	NF	NA	NA	NA	
METHACRYLATE	Skin Sens. 1;	Eye Irrit. 2		•			•		•	•	•		
000000000000000000000000000000000000000	7534-94-3	NA	231-403-1	≤ 3.0	NA	NA	NF	NF	NF	NA	NA	NA	
SOBORNYL METHACRYLATE		•	•	•	•	•							
00000001/4 AL 001/10/	67-63-0	NT8050000	200-661-7	≤ 2.0	400	500	400	500	NF	400	500	2000	400 TWA
SOPROPYL ALCOHOL	Flam. Liq. 2; §	Skin Irrit. 3; Eye Ir	rit. 2A; STOT SE	3; H225, F	1316, H	319							
TRIMETHYL PENTANYL	6846-50-0	SA1420000	229-934-9	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIISOBUTYRATE		•	•	•	•	•				•	•	•	•
POLYVINYL BUTYRAL	63148-65-2	NA	NA	≤ 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
	76-22-2	EX12250000	200-945-0	0.0-1.0	2	NA	12	19	NF	2	NA	200	
CAMPHOR	Flam. Sol. 2:	Acute Tox. 4; Skir			SE 3: F			315. H3		35			
ETHYTL TRIMETHYLBENZOYL	84434-11-7	INA	282-810-6	0.0-1.0	NA	NA	NF	NF	NF	NA	NA	NA	
PHENYL PHOSPHINATE		1		1	, .						_ · · · ·	1	

 $\mathbf{J} \cdot \mathbf{P} \cdot \mathbf{I}$ Page 2 of 7 **SAFETY DATA SHEET SDS-250** Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/8/2016 3. COMPOSITION & INGREDIENT INFORMATION - cont'd EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-STEL PEL STEL IDLH CHEMICAL NAME(S) CAS No. RTECS No. EINECS No. TWA PEAK OTHER STEL ETHYTL TRIMETHYLBENZOYL 84434-11-7 282-810-6 0.0-1.0 NA NA NF NF NF NA NA NA PHENYL PHOSPHINATE 947-19-3 0.0-0.3 NA NA NF NF NF NA NA NA HYDROXYCYCLOHEXYL PHENYL NA 213-426-9 KETONE Acute Tox. Oral 5; Aquatic Acute 3; H303, H402 205-029-4 0.0-0.3 NA NA NF NF NF NA NA NA 131-56-6 DJ0700000 BENZOPHENONE-1 9006-65-9 NA NA 0.0-0.3 NA NA NF NF NA NA NA NF DIMETHICONE 81-48-1 CB7700000 201-353-5 NA NA NF NF NA NA 0.0-0.3 NF CI 60725 (VIOLET 2) 0.0-0.3 NA NA NF NF NF NA NA NA 3567-66-6 NA 222-656-9 CI 17200 (RED 33) 4. FIRST AID MEASURES First Aid: DO NOT INDUCE VOMITING. If product has been swallowed, drink plenty of water or milk Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Seek immediate medical attention. Contact ChemTrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency telephone number for assistance and instructions. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Eyes: If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If irritation persists, seek medical attention. Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek Skin: prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned. Inhalation: Remove victim to fresh air at once. 42 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression. Slightly irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals. Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition & Ingredients) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). 4.3 Symptoms of Overexposure: Overexposure in eyes may cause redness, itching and watering. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Moderate irritation to eyes. Moderate irritation to skin near affected areas. Additionally, high concentrations of vapors 4.4 Acute Health Effects: can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 No harmful or chronic health effects are expected to occur from a single accidental ingestion. Target Organs: 4.6 Eyes, Skin, Respiratory System. Medical Conditions 47 None reported by the manufacturer. 1 **HEALTH** Aggravated by Exposure: Special Removal Instructions: Follow GelColor nail prep & removal instructions. Longer wear may increase removal time - soak nails 3 **FLAMMABILITY** longer. Do not force or pull gel away from nail or use metal implements/electric drill to remove product. If client experiences any 0 PHYSICAL HAZARDS sensation during removal (e.g. pressure, squeezing, pinching), remove wrap and gently file surface of gel only along side walls with PROTECTIVE EQUIPMENT В EDGE 240 File. Gently push off as much GelColor as possible with the Reusable Cuticle Stick. Resaturate foil wrap, rewrap nail, and **EYES** SKIN continue soaking. 5. FIREFIGHTING MEASURES Fire & Explosion Hazards:

5.1	Fire & Explosion Hazards:	Exothermic polymerization may cause containers to rupture. Cool containers with water to prevent polymerization. This product is a non-flammable liquid. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO ₂ , NO _x).
5.2	Extinguishing Methods:	CO ₂ , Halon (if permitted), Dry Chemical, Foam
5.3	Firefighting Procedures:	When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3[Y]E

Vapor Density:

Relative Density:

NA

1.4130 - 1.4190

9.10

9.11

Page 3 of 7 SAFETY DATA SHEET SDS-250 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/8/2016 6. ACCIDENTAL RELEASE MEASURES 6 1 Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Use ONLY non-sparking tools for recovery and clean-up. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., Work & Hygiene Practices: local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. 72 Storage & Handling: container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). Special Precautions: 7.3 Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OSHA OTHER FS. ppm (mg/m³) FS-STEL STEL PEAK STEL CHEMICAL NAME(S) TLV PEL **IDLH** TWA FTHYL ACETATE 400 TWA 400 NF NA 2000 400 200 400 NA SD ALCOHOL 40-B 1000 1900 1880 NF NF 1000 1900 3300 **BUTYL ACETATE** 150 150 200 1700 150 TWA 200 200 NF 200 HEPTANE NA 750 400 500 400 1640 NF 500 NITROCELLULOSE 400 400 400 NF NA 2000 400 TWA 200 NA ISOPROPYL ALCOHOL 400 500 400 500 NF 400 500 2000 400 TWA CAMPHOR NA 12 19 NF NA 200 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Controls: Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.4 Eve Protection: Avoid eye contact. Safety glasses with side shields should be used when handling this product. Hand Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. If anticipated that prolonged & 8.5 repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. Body Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. However, no special body protection 8.6 is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: 9.1 Clear to light pink/violet viscous liquid 92 Odor Acetate/Alcohol Odor 9.3 Odor Threshold: NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 NA 9.7 Flashpoint: 4.4 °C (40 °F) 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure: NA

$O \cdot P \cdot I$

SAFETY DATA SHEET

Page 4 of 7 SDS-250

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 9. PHYSICAL & CHEMICAL PROPERTIES - cont'd 9.12 Solubility Soluble 9 13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature ND Decomposition Temperature: 9.15 NA 9.16 300 - 500 cPs Other Information: 9.17 NA 10. STABILITY & REACTIVITY Stable under ambient conditions when stored properly (See Section 7, Storage and Handling). 10.1 Stability: 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and Products: carbon oxide gases (e.g., CO, CO₂). May occur, if exposed to extremely high temperatures. 10.3 Hazardous Polymerization: Open flames, sparks high heat, and direct sunlight. This product is incompatible with strong oxidizers (e.g., peroxides, 10.4 Conditions to Avoid superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). 10.5 Incompatible Substances: None known. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Absorption: YES Ingestion: YES 11.1 Toxicity Data: The product has not been tested for specific toxicity data 11.2 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: 11.4 See Section 4.5 11.5 Suspected Carcinogen: This product contains Isopropyl Alcohol which is not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC. 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans Teratogenicity This product is not reported to produce teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive effects in humans. Irritancy of Product: 11.7 See Section 4.3 11.8 Biological Exposure Indices: NF 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H₂O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K_{OW} = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals There is no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Dispose of in accordance with federal, state and local regulations Waste Disposal: 13.2 Special Considerations:

SAFETY DATA SHEET

Page 5 of 7 SDS-250

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

14.	TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L); or
		CONSUMER COMMODITY, ORM-D – until 12/31/2020
14.2	IATA (AIR):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 0.5 L); Or
		ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L)
14.3	IMDG (OCN):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L)
14.4	TDGR (Canadian GND):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)
14.5	ADR/RID (EU):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L)
14.6	SCT (MEXICO):	UN1263, PINTURA, 3, II (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)
14.7	ADGR (AUS):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L)





15. REGULATORY INFORMATION

10.1	Ortio (reporting requirements:	This product does contain isoproparior, butyl Acetate and Ethyl Acetate, substances subject to SARA Title III, Section
		313 reporting requirements.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity (RQ):	Butyl Acetate: 2,270 kg (5,000 lbs); Ethyl Acetate: 2,270 kg (5,000 lbs)
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the



DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid, D3 (Other Toxic Effects) State Regulatory Information: Butyl Acetate is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware

Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI).

Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA.

respiratory system. Safety Phrases (S): 2-7-16-24/25/26 - Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse

Isopropanol is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA.

Nitrocellulose is found on the following state criteria lists: DE, MA, and PA. Heptane is found on the following state criteria list: FL, MA, MN, PA and WA. Camphor is found on the following state criteria list: FL, MA, MN, PA and WA.

No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), or Wisconsin

Hazardous Substances List (WI).

The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Other Requirements: Ethyl Acetate: Flammable (F). Risk Phrases (R): 11-36/37/38 - Highly flammable. Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-16-23-29-33 - Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges. Butyl Acetate: Flammable (F). Risk Phrases (R): Flammable. Safety Phrases (S): 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Isopropanol: Flammable (F). Risk Phrases (R): 11-36/37 - Highly flammable. Irritating to eyes and

immediately with plenty of water and seek medical advice.





 $0.9 \cdot 1$

16.3

Disclaimer

SAFETY DATA SHEET

Page 6 of 7 SDS-250

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

16.1 Other Information:

WARNING! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES EYE IRRITATION. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/vapours/spray. Wash exposed skin areas thoroughly with soap and water after handling. Wear protective gloves/eye protection/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. For specific first aid treatment (See Section 4 of this Safety Data Sheet). Wash contaminated

immediately if irritation develops. KEEP OUT OF THE REACH OF CHILDREN.

16.2 Terms & Definitions: See last page of this Safety Data Sheet.

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

clothing before reuse. In case of fire, use CO₂, Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. For external use only. Do not ingest. Use only as directed. Discontinue use

16.4 Prepared for:

OPI Products, Inc.
13034 Saticoy Street
No. Hollywood, CA 91605 USA
Tel: +1 (818) 759-2400
Fax: +1 (818) 759-5776
http://www.opi.com

ShipMate, Inc.
P.O. Box 787
Sisters, Oregon 97759-0787 USA

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com $O \cdot P \cdot I$



SAFETY DATA SHEET

Page 7 of 7 SDS-250

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
CAS NO. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
TLV	Threshold Limit Value			
OSHA	U.S. Occupational Safety and Health Administration			
PEL Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health			

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

Α			
В	(Ell)		
С	ELA	THE SECOND SECON	
D	EA	THE SECOND SECON	
Е	ELA		
F			





Full Face Respirator

Splash Goggles



Face Shield &
Protective Eyewear

Protective Clothing

四



Synthetic Apron





Dust & Vapor Half-

e or

Airline Hood/Mask

or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition	Minimum temperature required to initiate combustion in air with no other				
Temperature source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive
TIVEL OIL	Tudiodolivo



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{io}	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{io} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log Kow or log Koc	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System			
DOT	U.S. Department of Transportation			
TC	TC Transport Canada			
EPA	U.S. Environmental Protection Agency			
DSL	Canadian Domestic Substance List			
NDSL	Canadian Non-Domestic Substance List			
PSL	Canadian Priority Substances List			
TSCA	U.S. Toxic Substance Control Act			
EU	European Union (European Union Directive 67/548/EEC)			
WGK	Wassergefährdungsklassen (German Water Hazard Class)			

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)		\odot	(1)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		*	¥		O	×	×
С	C E F		N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

				Pal la		\cdot		(
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment