# $0.9 \cdot 1$

# SAFETY DATA SHEET

Page 1 of 7 SDS-281

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 2/8/2016

1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	NICOLE BY OPI – QUICK DRY TOP COAT			
1.2	Chemical Name:	Solvent Mixture			
1.3	Synonyms:	NA			
1.4	Trade Names:	NI576			
1.5	Product Use:	Professional or Sundry Use Only			
1.6	Distributor's Name:	OPI Products, Inc.			
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA			
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)	•		
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776			

### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

WARNING! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS.

Classification: Flam. Liq. 2; Skin Irrit. 2A; Eye Irrit. 2B; STOT SE 3

<u>Hazard Statements</u> (H): H225 – Highly flammable liquid and vapor. H316 – Causes mild skin irritation. H319 – Causes serious eye irritation. H336 – May cause drowsiness or dizziness.

Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P240 – Ground/bond container and receiving equipment. P243 – Take precautionary measures against static discharge. P280 – Wear protective gloves/eye protection/face protection. P31+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 – Do not induce vomiting. P302+P352 – IF ON SKIN: Wash with plenty of soap and water. P332+P313 – If skin irritation occurs: Get medical advice/attention. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 – If eye irritation persist: Get medical advice/attention. P370+P378 – In case of fire, CO<sub>2</sub>, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



## 3. COMPOSITION & INGREDIENT INFORMATION

					-			IMITS IN AIR (mg/m³)					
					ACGIH		NOHSC		OSHA				
					pp	m	ppm		ppm				
0.1.5.4.0.1.1.1.1.5.(0.)		DTT00 11		2,			ES-	ES-	ES-				OTHER
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK NF	PEL	STEL	IDLH	400 TWA
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	15-40	400	400	200	400	INF	NA	NA	2000	400 TWA
		<del></del>	SE 3; H225, H31		100		400			100			1400 7144
SOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	10-30	400	500	400	500	NF	400	500	2000	400 TWA
		'	SE 3; H225, H31	· ·									1
CELLULOSE ACETATE BUTYRATE	9004-36-8	NA	NA	10-30	NA	NA	NF	NF	NF	NA	NA	NA	
SELECTORE NOT THE BOTTON	Acute Tox. Der	mal 4; H312											
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	10-30	150	200	150	200	NF	200	200	1700	100 NIOSH
BUTTLACETATE	Flam. Liq. 3; S	TOT SE 3; H226	, H336										
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	5-10	200	250	835	1040	NF	200	840	1700	
PROPILACEIATE	Flam. Liq. 2, Ey	ye Irrit. 2, STOT	SE 3; H225, H31	9, H336									
HEPTANE	142-82-5	MI7700000	205-563-8	1-5	400	500	400	1640	NF	400	500	750	
TEPTANE	Flam. Liq. 2; S	Flam. Lig. 2; Skin Irrit. 2; STOT-SE 3; Asp. 1; Aquatic Acute 1; Aquatic Chronic 2; H225, H304, H315, H336, H410											
4.0D\( 4.TEQ.00DQL\( 4.TED	25133-97-5	NA	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
ACRYLATES COPOLYMER	Skin Irrit.21; Eye Irrit. 2; Aquatic Chronic 4; H315, H319, H413												
	12738-64-6	NA	235-795-5	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
SUCROSE BENZOATE		1	- 1	1	1			1	1		1		l
	115-86-6	TC8400000	204-112-2	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENYL PHOSPHATE			e 1; H400, H410										
	131-56-6	DJ0700000	205-029-4	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	1
BENZOPHENONE-1			3; H315, H319,		14/7	14/1	1.41	141	141	14/7	14/7	11/1	<u> </u>
				0.1-1	NIA	NIA	NIE	NE	NE	NIA	NIA	NIA	
CI 60725 (VIOLET 2)	81-48-1	CB7700000	201-353-5	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	

 $0.6 \cdot 1$ 

# SAFETY DATA SHEET

Page 2 of 7 SDS-281

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 2/8/2016 4. FIRST AID MEASURES If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an 4 1 First Aid: Ingestion: unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm Eyes: water for at least 15 minutes. If irritation occurs, contact a physician. If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough Skin: washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. Inhalation: Remove victim to fresh air at once. 42 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression. Eyes: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. Skin: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). 4.3 Symptoms of Overexposure: Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. 4.4 Acute Health Effects: Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. Chronic Health Effects: 4.5 None known. 4 6 Target Organs: Eyes, Skin, Respiratory System. 4.7 Medical Conditions Aggravated by Exposure: Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 **PHYSICAL HAZARDS** 0 В PROTECTIVE EQUIPMENT **EYES** SKIN 5. FIREFIGHTING MEASURES DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, 5 1 Fire & Explosion Hazards: sparks & open flame. Keep container closed. Extinguishing Methods: 5.2 CO<sub>2</sub>, Halon (if permitted), Dry Chemical or Foam, as authorized. 5.3 Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3(Y)E Hazard Identification Number: 33 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing

promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers

and open bodies of water.

# SAFETY DATA SHEET

Page 3 of 7

**SDS-281** Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). Special Precautions: 7.3 Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION OTHER 8.1 **Exposure Limits:** NOHSC ppm (mg/m<sup>3</sup>) ES-ES-CHEMICAL NAME(S) STEL TWA STEL PEAK STEL IDLH ETHYL ACETATE 400 400 200 400 NF NA 2000 400 TWA ISOPROPYL ALCOHOL 400 500 400 500 NF 400 500 2000 400 TWA **BUTYL ACETATE** 150 TWA 150 200 150 200 NF 200 200 1700 PROPYL ACETATE 200 250 835 1040 NF 200 840 1700 **HEPTANE** 400 500 400 1640 NF 400 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Controls: Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 Hand Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. Body Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. However, no special body 8.6 protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Viscous liquid NA 9.3 Odor Threshold: ND 9.4 NA Melting Point/Freezing Point: 9.5 NA 9.6 Initial Boiling Point/Boiling NA Range: 9.7 - 4 °C (24 °F) estimated 9.8 Upper/Lower Flammability NF 9.9 Vapor Pressure: NA 9.10 Vapor Density: NΑ 9.11 Relative Density: 0.99 9.12 Solubility Insoluble 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature: NA Decomposition Temperature: 9.15 NA 9.16 Viscosity: > 1,200 cPs Other Information: 9.17 NA 10. STABILITY & REACTIVITY 10.1 Stability Stable under ambient conditions when stored properly (See Section 7, Storage and Handling). 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO<sub>2</sub>). 10.3 Hazardous Polymerization: May occur, if exposed to extremely high temperatures. 10.4 Conditions to Avoid: Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame. Incompatible Substances: 10.5 This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or

muriatic acids), or strong bases (e.g., lye, potassium hydroxide)

# $O \cdot P \cdot I$

# SAFETY DATA SHEET

Page 4 of 7 SDS-281

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 2/8/2016 11. TOXICOLOGICAL INFORMATION Inhalation: YES 11.1 Routes of Entry: Absorption: YES Ingestion: YES 11 2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Ethyl Acetate: LD<sub>50</sub> (oral, rat) = 5,620 mg/kg; LD<sub>50</sub> (oral, mouse) = 4,100 mg/kg; LC<sub>50</sub> (inh-6h, rat) = 16,000 ppm 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: 11.4 See Section 4.5 11.5 Suspected Carcinogen: This product contains Ethyl Acetate and Isopropyl Alcohol, which are not carcinogenic to humans, but are listed as Group 3 carcinogens by the IARC. Reproductive Toxicity: 11.6 No Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3 11.8 Biological Exposure Indices: NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Ethyl Acetate:  $K_{OC} = 0.73$ . Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K<sub>OC</sub> = 1.82. Water solubility: 120 parts H<sub>2</sub>O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K<sub>OW</sub> = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated halflife in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA Waste Number: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D - until 01/01/2021 IATA (AIR): 14.2 ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263, PAINT<u>, 3, II (IP VOL ≤ 1.0 L)</u> 14.3 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) 14.5 ADR/RID (EU): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): \* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)

 $0.9 \cdot 1$ 

# SAFETY DATA SHEET

Page 5 of 7 SDS-281

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 2/8/2016 15. REGULATORY INFORMATION This product contains Isopropanol, a substance subject to SARA Title III, Section 313 reporting requirements. 15.1 SARA Reporting Requirements: product contains Ethyl Acetate, a substance that is subject to SARA Title III, Section 304 reporting 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 **CERCLA Reportable Quantity** Ethyl Acetate: 2,270 kg (5,000 lbs); Butyl Acetate: 2,270 kg (5,000 lbs) 15.5 Other Federal Requirements This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects) State Regulatory Information: 15.7 Butyl Acetate is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI). Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA. Isopropanol is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA. Nitrocellulose is found on the following state criteria lists: DE, MA, and PA. Heptane is found on the following state criteria list: CA, NJ, PA, MN, MA, FL, and WA. Propyl Acetate is found on the following state criteria list: CA, MA, PA and NJ. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI) Other Requirements: The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: Ethyl Acetate: Flammable (F). Risk Phrases (R): 11-36/37/38 - Highly flammable. Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-16-23-29-33 - Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges. Butyl Acetate: Flammable (F). Risk Phrases (R): Flammable. Safety Phrases (S): 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Isopropanol: Flammable (F). Risk Phrases (R): 11-36/37 - Highly flammable. Irritating to eyes and respiratory system. Safety Phrases (S): 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Heptane: Highly Flammable (F) Harmful (XN). Risk Phrases (R): 11-38-50/53-65-67 - Highly flammable. Irritating to skin. Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. Safety Phrases (S): 16-29-33-9-60-61-62 - Keep away from sources of ignition - no smoking. Do not empty into drains. Take precautionary measures against static discharges. Keep container in a well-ventilated place. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Refer to special

instructions/safety data sheets. If swallowed, do not induce vomiting; seek medical advice

immediately and show this container or label.

 $0.9 \cdot 1$ 

# SAFETY DATA SHEET

Page 6 of 7 SDS-281

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 2/8/2016 16. OTHER INFORMATION DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES 16 1 Other Information: SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. Keep away from heat/sparks/open flame/hot surfaces - No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. **KEEP OUT OF REACH OF** CHILDREN. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910,1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: OPI Products, Inc. 13034 Saticoy Street ()·P·I No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com

# **SAFETY DATA SHEET**

Page 7 of 7 **SDS-281** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/8/2016

### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

### **GENERAL INFORMATION:**

CAS No. Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
TLV Threshold Limit Value				
OSHA U.S. Occupational Safety and Health Administration				
PEL Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health			

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard			
1	1 Slight Hazard			
2	2 Moderate Hazard			
3 Severe Hazard				
4	Extreme Hazard			

**HEALTH FLAMMABILITY** PHYSICAL HAZARDS PERSONAL PROTECTION

### PERSONAL PROTECTION RATINGS:

Α				
В				
С			THE STATE OF THE S	
D	(F)	(E)	THE STATE OF THE S	
Е				
F				























ð Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

## NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition   Minimum temperature required to initiate combustion in air with no of					
Temperature	source of ignition				
LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that v					
explode or ignite in the presence of an ignition source					
UEL Upper Explosive Limit - highest percent of vapor in air, by volume, that					
	explode or ignite in the presence of an ignition source				

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>Io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>io</sub> , LD <sub>io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(*)</b>	<b>(A)</b>		$\odot$	<b>®</b>		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compresse d	Flammabl e	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

## EC (67/548/EEC) INFORMATION:

V.**		M	*			×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammabl e	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

						<b></b>		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment