$0.9 \cdot 1$

SAFETY DATA SHEET

Page 1 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.4

SDS Revision Date: 2/8/2016

	1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	OPI GELSHINE BASE COAT				
1.2	Chemical Name:	Solvent Mixture				
1.3	Synonyms:	Gel Shine Base Coat				
1.4	Trade Names:	GS 300				
1.5	Product Use:	Cosmetic Use Only				
1.6	Distributor's Name:	OPI Products, Inc.				
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA				
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)				
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776				

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC and ADG Code (Australia).

DANGER! HIGHLY FLAMMMABLE LIQUID AND VAPOUR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

Classification: Flam. Liq. 2, Skin Sens. 1, Eye Irrit. 2A

<u>Hazard Statements</u> (H): H225 – Highly Flammable liquid and vapor. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation.

Precautionary Statements (P): P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs - Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO2, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					ACGIH		NOHSC		OSHA				
					pp	m		ppm			ppm		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	10-30	400	400	200	400	NF	NA	NA	2000	400 TWA
EINTLACETATE	Flam. Liq. 2; I	ye Irrit. 2; STOT	SE 3; H225, H3	19, H336									
ETHANOL (CD ALCOHOL 40D)	64-17-5	KQ6300000	200-578-6	10-30	1000	1900	1880	NF	NF	1000	1900	3300	
ETHANOL (SD ALCOHOL 40B)	Flam. Liq. 2; I	1225	•										
DI-HEMA TRIMETHYLHEXYL	72869-86-4	NA	276-957-5	10-30	NA	NA	NF	NF	NF	NA	NA	NA	
DICARBAMATE		1	I.							ı	l	ı	1
DUTY AGETATE	123-86-4	AF73500000	204-658-1	10-30	150	200	150	200	NF	200	200	1700	150 TWA
BUTYL ACETATE	Flam. Liq. 3;	Acute Tox. 5; Ski	n Irrit. 2; Eye Irrit	: 2A, STOT	-SE 3; /	Acute A	q. 3; Cl	ron. Ad	a. 3; H2	26, H3	15, H31	9, H33	3, H336, H412
HEDTANE	142-82-5	MI7700000	205-563-8	5-10	400	500	400	1640	NF	500	NA	750	
HEPTANE	Flam. Liq. 2;	Flam. Liq. 2; Skin Irrit. 2; STOT-SE 3; Asp. 1; Aquatic Acute 1; Aquatic Chronic 2; H225, H304, H315, H336, H410											
NITROCELLULOSE	9004-70-0	AH5425000	NA	1-5	400	400	400	200	NF	NA	NA	2000	
NI KOCELLULOSE	Flam. Liq. 2; I												
TOSYLAMIDE EPOXY RESIN	25035-71-6	QW0970000	NA	1-5	NA	NA	NA	NA	NA	NA	NA	NA	
1001 LAWIDE LI OXI RESIN													
HYDROXYETHYL METHACRYLATE	868-77-9	OZ4725000	212-782-2	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
(HEMA)	Eye Irrit. 2; Skin Irrit. 2; Skin Sens. 1; H319, H315, H317												
HYDROXYPROPYL	27813-02-1	UD3442500	248-666-3	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
METHACRYLATE	Skin Sens 1:	Skin Sens.1; Eye Irrit.2; H317, H319											
	7534-94-3	NA	231-403-1	1-5	NA	NA	NF	NF	NF	NA	NA	NA	I
ISOBORNYL METHACRYLATE		1	1==: .00 1	1									1
	67-63-0	NT8050000	200-661-7	1-5	400	500	400	500	NF	400	500	2000	400 TWA
ISOPROPYL ALCOHOL		Skin Irrit. 3; Eye Ir			1316. H	319							1
TRIMETHYL PENTANYL	6846-50-0	SA142000	229-937-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
DIISOBUTYRATE		•	· ·		•								•
DOLLA MANA DI ITADA	63148-65-2	TR49550000	NA	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
POLYVINYL BUTYRAL													

SAFETY DATA SHEET

Page 2 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.4 SDS Revision Date: 2/8/2016 3. COMPOSITION & INGREDIENT INFORMATION - cont'd EXPOSURE LIMITS IN AIR (mg/m³) **ACGIH** NOHSC OSHA ppm ppm ppm ES-ES-IDLH CHEMICAL NAME(S) CAS No. RTECS No. EINECS No. STEL TWA PEAK STEL OTHER NF 947-19-3 NA 213-426-9 NF NF 1-5 NA NA NA HYDROXYCYCLOHEXYL PHENYL NA NA KETONE Acute Tox. Oral 5; Aquatic Acute 3; H303, H402 76-22-2 EX1225000 200-945-0 0.1-1 2 4 2 12 NF NA NA 200 **CAMPHOR** Flam. Sol. 2, Acute Tox. 4, STOT SE 2; H228, H332, H371 NA NF NF NF NA NA NA ETHYTL TRIMETHYLBENZOYL 84434-11-7 NA 282-810-6 0.1-1 NA PHENYL PHOSPHINATE NF 81-48-1 CB7700000 201-353-5 0.1-1 NA NA NF NA NA NA NF CI 60725 (VIOLET 2) 131-56-6 DJ0700000 205-029-4 0-0.1 NA NA NF NF NF NA NA NA BENZOPHENONE-1 Sin Irrit. 2; Eye Irrit. 2; STOT SE 3; H315, H319, H335 9006-65-9 NA 0-0.1 NA NA NF NF NF NA NA NA NA DIMETHICONE NA 222-656-9 0-0.1 NA NA NF NF NF NA NA NA 3567-66-6 CI 17200 (RED 33) 4. FIRST AID MEASURES 4.1 First Aid: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water Eyes: for at least 15 minutes. If irritation occurs, contact a physician. If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough Skin: washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. Inhalation: 4.2 Effects of Exposure: Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Eyes: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. Skin: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, naus<u>ea)</u>. 4.3 Symptoms of Overexposure: Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. Irritation of the nose and throat, skin irritation, signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination and/or fatigue) Acute Health Effects: 4.4 Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea Chronic Health Effects: 4.5 None known. Target Organs: 46 Eyes, Skin, Respiratory System. 4.7 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В **EYES** SKIN 5. FIREFIGHTING MEASURES WARNING! FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & 5.1 Fire & Explosion Hazards: open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Fine mist or sprays may be flammable at temperatures below the flashpoint. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, Water Fog, CO₂, Halon (if permitted), Dry Chemical, Foam HazChem Code: 3[Y] E Hazard 5.2 Extinguishing Methods: Identification Number: 33

SAFETY DATA SHEET

Page 3 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.4 SDS Revision Date: 2/8/2016 5. FIREFIGHTING MEASURES - cont'd 5.3 Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For <u>large spills</u> (e.g., \geq 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). 7.3 Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: ACGIH NOHSC OTHER 8.1 ppm (mg/m³) ES-FS-CHEMICAL NAME(S) TWA STEL PEAK PEL ETHYL ACETATE 400 NF 400 TWA 400 400 200 NA NA 2000 ETHANOL (SD ALCOHOL 40B) 1000 1880 1900 1900 NF NF 1000 3300 **BUTYL ACETATE** 150 200 150 200 NF 200 200 1700 150 TWA **HEPTANE** 400 500 400 1640 NF 500 NA 750 NITROCELLULOSE 400 400 400 200 NF NA NA 2000 ISOPROPYL ALCOHOL 400 500 400 500 NF 400 500 2000 400 TWA 12 NF NA NA 200 Ventilation & Engineering 8.2 When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.4 Eye Protection: Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8.5 Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: No special body protection is required under typical circumstances of use and handling. necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.

SAFETY DATA SHEET

Page 4 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Viscous Liquid 92 Odor Ester (Fruity) Odor 9.3 Odor Threshold: NA 9.4 NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 NA Range: 9.7 Flashpoint: NA 9.8 Upper/Lower Flammability NA 99 Vapor Pressure: NA 9.10 Vapor Density: NA 9.11 Relative Density: NA Solubility: 9.12 Insoluble Partition Coefficient (log Pow): 9.13 NA 9.14 Autoignition Temperature NA 9.15 Decomposition Temperature: NA 9.16 300 - 800 cPs 9.17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability: Stable under ambient conditions when stored properly (See Section 7, Storage and Handling) 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritation vapors and Products: carbon oxide gases (e.g. CO, CO₂). 10.3 Hazardous Polymerization: May occur if exposed to extremely high temperatures. 10.4 Conditions to Avoid High temperatures and incompatible substances. 10.5 Incompatible Substances: Strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide). 11. TOXICOLOGICAL INFORMATION 11.1 Routes of Entry: Inhalation: YES Absorption: YES Inaestion: YES 11.2 Toxicity Data: This product has not been tested on animals to obtain toxicology data. There is toxicology data for some components of the product, which are found in scientific literature. This data is presented below: Ethyl Acetate: LD₅₀ (oral, rat) = 11,300 mg/kg; Butyl Acetate: LD₅₀ (oral, rat) = 11,400 mg/kg; Isopropyl Alcohol: LD₅₀ (oral, rat) = 5,840 mg/kg;11.3 Acute Toxicity: See Section 4.4 11.4 Chronic Toxicity: See Section 4.5 11.5 Suspected Carcinogen: This product contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as Group 3 carcinogen by IARC. Reproductive Toxicity: 11.6 This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to cause mutagenic effects in humans. Embryotoxicity This product is not reported to cause embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product: See Section 4.3 Biological Exposure Indices: 11.8 NA 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/L. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H₂O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K_{OW} = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated halflife in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. Effects on Plants & Animals: There are no specific data for this product. 12.3 Effects on Aquatic Life There are no specific data available for this product; however, very large releases of this product may be harmful or fatal

to overexposed aquatic life.

SAFETY DATA SHEET

Page 5 of 7 **SDS-340**

Prepa	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.4 SDS Revision Date: 2/8/2016							
	13. DISPOSAL CONSIDERATIONS							
13.1	Waste Disposal:			vogulations				
13.2	Special Considerations:	Waste disposal must be in accordance with appropr U.S. EPA Waste Number: D001 (characteristic - igni		regulations.				
	O.O. EL A Waste Hamber. Doo't (offaracteristic lightable)							
	14. TRANSPORTATION INFORMATION							
	The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.							
14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0						
		UN1263, PAINT, 3, II	•					
14.2	IATA (AIR):	CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0. UN1263, PAINT, 3, II	5 L)					
14.3	IMDG (OCN):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II		PLANMARIE LIGOR				
14.4	TDGR (Canadian GND):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II		PLIMINE LUDY 3				
14.5	ADR/RID (EU):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)						
		UN1263, PAINT, 3, II						
14.6	SCT (MEXICO):	UN1263, PINTURA, 3, II, (CANTIDAD LIMITADA, IF UN1263, PINTURA, 3, II	⁹ VOL ≤ 1.0 L)					
14.7	ADGR (AUS):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II						
* This	product may also be shippe	d as an Excepted Quantity (Inner Package Volume ≤ 30 mL,	Total Quantity ≤ 500 mL per Oute	er Package)				
		15. REGULATORY IN	FORMATION					
15.1	SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4) – Butyl Acetate, I subject to SARA Title III (313) reporting and 40 CFR	Ethyl Acetate. This product	contains <u>Isopropyl Alcohol</u> , a substance				
15.2	SARA Threshold Planning	There are no specific Threshold Planning Quantities		roduct.				
15.3	Quantity: TSCA Inventory Status:	The components of this product are listed on the TS	CA Inventory					
15.4	CERCLA Reportable Quantity	Butyl Acetate: 2,270 kg (5,000 lbs); Ethyl Acetate: 2,						
15.5	(RQ): Other Federal Requirements:	This product complies with the appropriate section (Cosmetics).	ns of the Food and Drug /	Administration's 21 CFR subchapter G				
15.6	Other Canadian Regulations:	This product has been classified according to the hall of the information required by the CPR. The DSL/NDSL. None of the components of this productions of the components of the productions of the components.	components of this produc	et are listed on the				
		WHMIS Class B2 Flammable Liquid.						
15.7	State Regulatory Information:	Butyl Acetate is found on the following state criter Quality Management List (DE), Massachusetts Hazz (MN), New Jersey Right-to-Know List (NJ), New Yor (PA), and Washington Permissible Exposures List (NG)	ardous Substances List (MA) rk Hazardous Substances Lis VA).	, Minnesota Hazardous Substances List st (NY), Pennsylvania Right-to-Know List				
		Ethyl Acetate is found on the following state criteria Substances List (WI).	lists: CA, DE, MA, MN, NJ,	NY, PA, WA, and Wisconsin Hazardous				
		Heptane is found on the following state criteria list: F Nitrocellulose is found on the following state criteria						
		Isopropyl Alcohol is found on the following state crite		· ·				
		No other ingredients in this product, present in a cor criteria lists: California Proposition 65 (CA65), Del						
		List (FL), Massachusetts Hazardous Substances Lis	t (MA), Michigan Critical Sub	ostances List (MI), Minnesota Hazardous				
		Substances List (MN), New Jersey Right-to-Know I Right-to-Know List (PA), Washington Permissible Ex						
15.8	Other Requirements:	The primary components of this product are listed in						
		Isopropyl Alcohol: Flammable, Irritant (F, Xi);						
		Flammable, Irritant (F, Xi). Risk Phrases (R) – I swallowed. Irritating to eyes. Vapors may cause						
		may cause skin dryness and cracking. Safety Phra	ases (S): S1/2-7/9-16-20/21-2	24/25-26-28-33-46 -				
		Keep locked up and out of the reach of children ventilated place. Keep away from sources of ignitio						
		contact with skin and eyes. In case of contact with	eyes, rinse immediately with	plenty of water and				
		seek medical advice. After contact with skin, was precautionary measures against static discharges.						
		and show this container or label.	·					
		Hydroxyethyl Methacrylate: Irritant (Xi).Risk Phrases system. Safety Phrases (S): S(2)-26-28 – Keep ou	t of the reach of children. In	case of contact with				
		eyes, rinse immediately with plenty of water and see immediately with plenty of soap and water.	ek medical advice. After con	tact with skin, wash				
i –								

 $0.9 \cdot 1$

SAFETY DATA SHEET

Page 6 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.4 SDS Revision Date: 2/8/2016 16. OTHER INFORMATION DANGER! HIGHLY FLAMMMABLE LIQUID AND VAPOUR. MAY CAUSE AN ALLERGIC SKIN REACTION. 16 1 Other Information: CAUSES SERIOUS EYE IRRITATION. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. For specific first aid treatment (See Section 4 of this Safety Data Sheet). Wash contaminated clothing before reuse. In case of fire, CO2, Halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: **OPI Products. Inc.** 13034 Saticov Street .P.T No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com Prepared by: ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600

> Fax: +1 (310) 370-5700 http://www.shipmate.com

SAFETY DATA SHEET

Page 7 of 7 **SDS-340**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/8/2016

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number		

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
TLV	TLV Threshold Limit Value	
OSHA	U.S. Occupational Safety and Health Administration	
PEL	PEL Permissible Exposure Limit	
IDLH Immediately Dangerous to Life and Health		

FIRST AID MEASURES.

TIKOT AID MEAGORES.					
CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.				

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	

HEALTH FLAMMABILITY PHYSICAL HAZARDS PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В			
С		H, III	
D	(EV)	THE STATE OF THE S	
Е			
F		THE PERSON NAMED IN COLUMN TO PERSON NAMED I	







Full Face Respirator



Face Shield &

Protective Clothing & Full Suit

Dust Respirator

Dust & Vapor Half-

Synthetic Apron

Full Face Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
ОХ	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC _o , LC _{io} , & LC _o	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	*	(4)		\odot	(18)		(K)
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

11.4		M	*		&	X	X
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment