

Page 1 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 6/1/2015

	1. PRODUCT & COMPANY IDENTIFICATION				
1.1	Product Name:	BALAYAGE LIGHTENER			
1.2	Chemical Name:	Persulfate Blend Hair Bleach			
1.3	Synonyms:	Blend 1427			
1.4	Trade Names:	BALAYAGE LIGHTENER			
1.5	Product Uses & Restrictions:	Professional Cosmetic Use Only			
1.6	Distributor's Name:	Hair Systems, Inc.			
1.7	Distributor's Address:	30 Park Avenue, Englishtown, NJ 07726 USA			
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 10069)			
1.9	Business Phone / Fax:	+1 (732) 446-2202 / +1 (732) 446-7968			

### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! MAY INTENSIFY FIRE; OXIDIZER. HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE RESPIRATORY IRRITATION.

<u>Classification</u>: Oxidizing Solid – Category 3; Acute Toxicity – Category 4; Skin Irritation – Category 2; Eye Irritation – Category 2A; Respiratory Sensitization – Category 1; Skin Sensitization – Category 1; Single Target Organ Toxicity (Single Exposure).

<u>Hazard Statements</u> (H): H272 – May intensify fire; oxidizer. H302 – Harmful if swallowed. H315 – Causes skin irritation. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H334 – May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 – May cause respiratory irritation.

Precautionary Statements (P): P210 - Keep away from heat/sparks/open flames/hot surfaces - No smoking. P220 - Keep/Store away from clothing/cotton/combustible materials. P261 - Avoid breathing dust/fumes. P264 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P284 - If necessary, wear respiratory protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302+P352 - IF ON SKIN: Wash with soap and water. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P321 -Specific treatment (see section 4 of the Safety Data Sheet or the product label). P330 - Rinse mouth. P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or a rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists get medical advice/attention. P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P362+P364 - Take off contaminated clothing and wash before reuse. P370+P378 - In case of fire: Use CO2, Halon (if permitted), dry chemical, or foam for extinction. P403+P233 - Store in a well ventilated place. Keep container tightly closed. P405 -Store locked up. P501 - Dispose of contents/container to licensed treatment, storage or disposal facility (TSDF).



## 3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					ACGIH		SIH NOHSC				OSHA		
					pp	ppm ppm			ppm				
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
AMMONIUM PERSULFATE	7727-54-0	SE0350000	231-786-5	1-10	(0.1)	NA	NF	NF	NF	NA	NA	NA	
AMMONIOW PERSULFATE	Ox. Sol. 3; Acu	ute Tox. 4; Skin Ir	rit. 2; Skin Sens.	1; Eye Irrit	. 2; Res	p. Sen	s. 2; H2	72, H3	02, H31	5, H31	7, H319	, H334,	,H335
	7727-21-1	SE0400000	231-781-8	1035	(0.1)	NA	NF	NF	NF	NA	NA	NA	
POTASSIUM PERSULFATE	Ox. Sol. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; Resp. Sens. 1; Skin Sens. 1; STOT SE 3; H272, H302, H315, H317, H319, H334,												
	H335												
SODIUM METASILICATE	6834-92-0	VV9275000	229-912-9	1-10	NA	NA	NF	NF	NF	NA	NA	NA	
SODIOW WETASILICATE	Acute Tox. 4; Skin Corr. 1B; Serious Eye Dam. 1; STOT SE 3; H302, H314, H335												
SUPREME (KAOLIN)	1332-58-7		310-194-1	15-25	NA	NA	NF	NF	NF	(2)	NA	NA	
SUPREIVIE (KAULIN)													
MACNICULIA CARRONATE	546-93-0		208-915-9	30-45	NA	NA	NF	NF	NF	NA	NA	NA	
MAGNESIUM CARBONATE													
	NA	NA	NA	BAL	NA	NA	NF	NF	NF	NA	NA	NA	
PROPRIETARY BLEND		1	1										
	L.												



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 6/1/2015

Prepa	ared to OSHA, ACC, ANSI, N	OHSC, WHMIS, GHS & EU Standards SDS Revisi	ion: 1.0   SDS Revision Date: 6/1/2015
		4 FIRST AIR MEASURES	
	1	4. FIRST AID MEASURES	
4.1	First Aid:	Ingestion:  If ingested, do not induce vomiting. Drink plenty of war offer plenty of water or milk. Never give water or milk ingested, contact the nearest Poison Control Center or the time and amount of the substance that was swallowe  Eyes:  If product is in the eyes, flush with copious amounts of lenses if present and easy to do, continue flushing. irrigation. If problem persists, consult a physician.  Skin:  If redness, dryness or other signs of irritation to the skin affected skin areas with plenty of warm water and soap.	to an unconscious person. If large quantities are local emergency number. Provide an estimate of ed. Get medical attention immediately. If water for at least 15 minutes. Remove contact Open and close eyelid(s) to ensure thorough develop, remove contaminated clothing and wash
4.2	Effects of Exposure:	Inhalation: Give oxygen as necessary and get medical attention.  Ingestion: May cause irritation in mouth and throat. Swallowing minjury by distention of the esophagus or stomach. May cause irritation, redness, stinging and tearing. Where the developers, the resulting mixture may cause severe eye May be irritating to skin, especially after prolonged contaction.  Inhalation: Prolonged exposure may cause irritation in nose and the breathing. Excessive inhalation of dust may result in second cause asthma-like symptoms in some sensitive individual	ause nausea, vomiting and diarrhea. hen bleach powders are mixed with peroxides or irritation and possible eye injury. act. The product can cause allergic skin reactions ted exposure. iroat with chest discomfort, coughing and difficulty ensitization and irritation to respiratory tract. May
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure may include redness, itching, and ir may cause redness, itching and watering. The product can cause alle upon prolonged or repeated exposure.	
4.4	Acute Health Effects:	Moderate irritation to skin near affected areas. This product causes se	erious eye irritation.
4.5	Chronic Health Effects:	The material may accentuate any pre-existing dermatitis condition.	
4.6	Target Organs:	Eyes, skin & respiratory system.	
4.7	Medical Conditions Aggravated by Exposure:	Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be aggravated.	HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARDS 1 PROTECTIVE EQUIPMENT B EYES SKIN
		5. FIREFIGHTING MEASURES	
5.1	Fire & Explosion Hazards:  Extinguishing Methods:	DANGER! MAY INTENSIFY FIRE; OXIDIZER. Upon decomposition and may thereby stimulate combustion of flammable and combustible with media appropriate for the burning material. Product contains of product on towels, sponges or mops may cause fire. Rinse towels Rinse sponges and mops thoroughly before storage. Persulfate of undergo decomposition in the presence of moisture and heat. Sprimaterial with large quantities of water.  CO <sub>2</sub> , Halon (if permitted), Dry Chemical, Foam, as authorized. Water Class A or Class B extinguisher should be sufficient for the product. Extinguisher should also be appropriate to address the location of the	de materials. Extinguish fires exidizing materials. Residual thoroughly before disposal. compounds may ignite and ray and flood decomposing der and/or foam – typically a However, selection of a fire fire and equipment involved.
5.3	Firefighting Procedures:	Flood with water and use water spray to cool fire-exposed containers at This product is an oxidizer and may intensify fire. As in any fire, we self-contained breathing apparatus (pressure-demand) and full protect cool until well after the fire is out. Use water spray to cool fire-exposersonnel. Prevent runoff from fire control or dilution from entering se supply, or any natural waterway. Firefighters must use full bunker geat positive pressure self-contained breathing apparatus to protect a decomposition products.  HazChem Code: 2P  Hazard Identification Number: 50	ear MSHA/NIOSH approved ctive gear. Keep containers osed surfaces and to protect ewers, drains, drinking water ar including NIOSH-approved
		6. ACCIDENTAL RELEASE MEASUR	RES
6.1	Spills:	Before cleaning any spill or leak, individuals involved in spill clean Equipment. Plastic or rubber gloves, respirator, eye protection and appendix (e.g., ≤ 1.0 lbs (0.45 kg)). Wear appropriate protective explored in a non-combustible material such as vermiculite or sand to soak undisposal. Do not use water or a material such as "speedy dry" to sparking materials (e.g., plastic brooms, shovels, dustpans) and platanother container.  Large Spills: (e.g., > 1.0 lbs (0.45 kg)) Keep incompatible materials upwind and away from spill or release. Isolate immediate hazard are Stop spill or release if it can be done with minimal risk. Wear approprotection as conditions warrant.	nup must wear appropriate Personal Protective pron may be required for clean-up of large spills. quipment including gloves and protective eyewear. up the product and place into a container for later soak up material. Sweep up material using nonace into a plastic container or plastic liner within (e.g., organics such as oil) away from spill. Stay ea and keep unauthorized personnel out of area.



Page 3 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 6/1/2015

	T	7. HANDLIN									
7.1	Work & Hygiene Practices:	Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Avoid contact with flammable or combustible materials. Avoid contamination from any source, including metals, dust and organic materials. Keep bulk materials covered. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.									
7.2	Storage & Handling:	local exhaust ventilation, fan away from incompatible subs	Geep this material away from heat, sparks and open flame. Use and store in a cool, dry, well-ventilated location (e.g., ocal exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F (49 °C). Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying keep tap in place when not in use. Store away from incompatible materials (see Section 10).								
7.3	Special Precautions:	Spilled material may present to come into contact with m utensils inside containers of p	oisture	(keep I							
		8. EXPOSURE CO	NTR	OLS	& PER	SONA	L PRO	ECT	ION		
8.1	Exposure Limits:		AC	GIH		NOHSC			OSHA		OTHER
	ppm (mg/m³)	CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		KAOLIN	NA	NA	NF	NF	NF	(2)	NA	NA	
		POTASSIUM PERSULFATE	(0.1)	NA	NF	NF	NF	NA	NA	NA	
8.2	Ventilation & Engineering Controls:	AMMONIUM PERSULFATE  When working with large qual exposure below the airborne	(0.1) ntities o exposu	NA of production re limits	NF ct, provide s. Ensure	NF adequate that an ey	NF ventilation ewash stat	NA (e.g., Ic ion, sinl	NA ocal exh k or was	NA aust ven shbasin	l tilation, fans), to keep is available in case o
8.3	Respiratory Protection:	exposure to eyes.  No special respiratory protection necessary, use only respirat §1910.134, or applicable Uprovinces, F.C. member state	ory pro	tection e regul	authorized	per U.S.	OSHA's r	equiren	nent in	29 CFR	
8.4	Eye Protection:	Avoid contact. Wear protect handling this product. Alwa	provinces, E.C. member states, or Australia.  Avoid contact. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.								
8.5	Hand Protection:	If anticipated that prolonged latex or rubber gloves for r	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.								
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. Wear appropriate protective clothing to prevent skin contact, (e.g., boots, lab coat, apron, coveralls) as needed. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.									
		9. PHYSIC	A I O	CHE	MICAL	DDOI	DEDTIE	•			
9.1	Appearance:	Free flowing powder	AL &	CHE	MICAL	. PROF	EKIIE	<u> </u>			
9.2	Odor:	Bleach odor (no fragrance ad	ded)								
9.3	Odor Threshold:	NA	<u>-</u>								
9.4	pH:	9-11.5									
9.5	Melting Point/Freezing Point:	NA									
9.6	Initial Boiling Point/Boiling Range:	NA									
9.7	Flashpoint:	NA									
9.8	Upper/Lower Flammability Limits:	NA									
9.9	Vapor Pressure:	NA									
9.10	Vapor Density:	NA .									
9.11	Relative Density:	< 0.5									
9.12	Solubility:	4.7 g in 100 mL water									
9.13 9.14	Partition Coefficient (log Pow):  Autoignition Temperature:	NA NA									
	Decomposition Temperature:	NA									
9.15	l ' '										
9.15 9.16	Viscosity:	NA									



ADGR (AUS):

14 7

# SAFETY DATA SHEET

Page 4 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards SDS Revision Date: 6/1/2015 10. STABILITY & REACTIVITY Stability: Unstable. Gradually decomposes losing oxygen. Decomposes more rapidly at higher temperatures. Metals other than stainless steel are apt to cause decomposition of persulfate solutions. Generates heat when mixed with acid. May react with ammonium salt solutions resulting in evolution of ammonia gas. Liberation of oxygen gas may result in dangerous pressures If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic 10.2 Hazardous Decomposition gases (e.g., CO, CO<sub>2</sub>, and SO<sub>2</sub>). Liberation of gas (e.g., oxygen) may result in dangerous pressures. Decomposed by moisture to form oxygen and ozone. Burning may produce nitrogen oxides, sulfur oxides, and sulfuric acid. 10.3 Hazardous Polymerization: Will not occur. Open flames, sparks, high heat and direct sunlight. Moisture, combustible material, heat, flame, ignition sources, shock, Conditions to Avoid 10.4 friction, powdered metals, phosphorus, hydrides, organic matter, halogens, acids, alkalis, and incompatibles. Incompatible Substances: Reducing agents, organics, some acids, flammable materials. Do not use metallic bowls or utensils when mixing this 10.5 product. Avoid contamination with moisture, combustible or organic materials (e.g., sawdust, damp paper towels). 11. TOXICOLOGICAL INFORMATION Inhalation: YES Routes of Entry Absorption: YES Ingestion: YES 11 1 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product but is not presented in this document. 11.3 Acute Toxicity: Moderate irritation to skin near affected areas. This product causes serious eye irritation. 11.4 Chronic Toxicity: The material may aggravate any pre-existing skin condition (e.g., dermatitis). This product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. 11.5 Suspected Carcinogen: 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure Biological Exposure Indices: 11.8 NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are available, but are not presented in this Safety Data Sheet. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: This product was not tested on animals. Specific aquatic test data is available for the some of the components of this product, but are not presented in this Safety Data Sheet 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Waste disposal must be in accordance with appropriate Federal, state, and local regulations 13.2 Special Considerations: U.S. EPA Waste Number: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg); or CONSUMER COMMODITY, ORM-D - until 01/01/2021 14.2 IATA (AIR): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 1.0 kg) 14.3 IMDG (OCN): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg) 14.4 TDGR (Canadian GND): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 5.0 kg) 14.5 ADR/RID (EU): UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III (LTD QTY, IP VOL ≤ 5.0 kg) 14 6 SCT (MEXICO): UN1479, SOLIDO COMBURENTE, N.E.P. (persulfato de potasio, persulfato de ammonia), 5.1, III

UN1479, OXIDIZING SOLID, N.O.S. (potassium persulfate, ammonium persulfate), 5.1, III

(CANTIDAD LIMITADA, IP VOL ≤ 5.0 kg)

(LTD QTY, IP VOL  $\leq$  5.0 kg)



Page 5 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 6/1/2015

		15. REGULATORY INFORMATION					
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.					
15.2	SARA Threshold Planning Qty:	There are no specific Threshold Planning Quantities for the components of this product.					
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.					
15.4	CERCLA Reportable Quantity:	NA					
15.5	Other Federal Requirements:	This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.					
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS C, D2B (Oxidizing Agent, Other Toxic Effects)					
15.7	State Regulatory Information:	Potassium Persulfate is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), and Pennsylvania Right-to-Know List (PA).  Ammonium Persulfate is found on the following state criteria lists: NJ and PA.  No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).					
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:  Potassium Persulfate: Oxidizer, Harmful (O, Xn). Risk Phrases (R): 8-22-36/37/38-42/43 — Contact with combustible material may cause fire. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Safety Phrases (S): (2)-3-7-17-22-24-26-37-51 - Keep out of the reach of children. Keep in a cool place. Keep container tightly closed. Keep away from combustible material. Do not breathe dust. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in well-ventilated areas.  Ammonium Persulfate: Oxidizer, Harmful (O, Xn). Risk Phrases (R): 8-22-36/37/38-42/43 — Contact with combustible material may cause fire. Harmful if swallowed. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact. Safety Phrases (S): (2)-3-7-17-22-24-26-37-51 - Keep out of the reach of children. Keep in a cool place. Keep container tightly closed. Keep away from combustible material. Do not breathe dust. Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Use only in well-ventilated areas.					



Page 6 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision: 1.0

SDS Revision Date: 6/1/2015

		16. OTHER INFORMATION				
16.1	Other Information:	DANGER! MAY INTENSIFY FIRE; OXIDIZER. HARMFUL IF SWALLOWED. CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. Keep away from heat/sparks/open flames/hot surfaces — No smoking. Keep/Store away from clothing/cotton/combustible materials. Avoid breathing dust/fumes. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If necessary, wear respiratory protection. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do — continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see section 4 of the Safety Data Sheet or the product label) Rinse mouth. If skin irritation occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash before reuse. In case of fire: Use CO2, Halon (if permitted), dry chemical, or foam for extinction. Store in a well ventilated place. Keep container tightly closed. Store locked up. KEEP LOCKED UP AND OUT OF REACH OF CHILDREN				
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.				
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Hair Systems knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.				
16.4	Issued by:	Hair Systems, Inc. 30 Park Avenue Englishtown, NJ 07726 USA Tel: +1 (732) 446-2202 Fax: +1 (732) 446-7968 http://www.hairsystemsinc.com				

Page 7 of 7

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & EU Standards

SDS Revision Date: 6/1/2015

**FLAMMABILITY** 

# **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number
EXPOSURE	LIMITS IN AIR:
ACGIH	American Conference on Governmental Industrial Hygienists
С	Ceiling Limit
ES	Exposure Standard (Australia)
IDLH	Immediately Dangerous to Life and Health
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

#### FIRST AID MEASURES:


Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

#### HMIS-III HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



#### PERSONAL PROTECTION RATINGS:









Splash Goggles









Synthetic Apron



**Full Face Respirator** 



**Full Face** Respirator

Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:


* · · · · · · · · · · · · · · · · · · ·				
ML	Maximum Limit			
mg/m3	milligrams per cubic meter			
NA	Not Available			
ND	Not Determined			
NE	Not Established			
NF	Not Found			
NR	No Results			
ppm	parts per million			
SCBA	Self-Contained Breathing Apparatus			

## NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:					
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

#### **HAZARD RATINGS:**

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			
ACD	Acidic			
ALK	Alkaline			
COR	Corrosive			
₩	Use No Water			
OX	Oxidizer			
TREFOIL	Radioactive			
TOXICOLOGICAL INFORMATION:				



TD <sub>lo</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
$TD_lo,LD_lo,\&LD_oor$ $TC,TC_o,LC_lo,\&LC_o$	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NOHSC	National Occupational Health and Safety Commission (Australia)				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				
HMIS-III	National Paint & Coatings Association Hazardous Materials Identification System				

## WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(4)</b>	<b>(2)</b>		<b>(T)</b>	<b>®</b>		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### EC (67/548/EEC) INFORMATION:

			*		<b>S</b>	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$			<b>\_</b>		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment